

Product

BULB-B22/01 34LED



LED NUMBER: 34
Size: Par-25
85mm Daimeter
100mm tall

FEATURES:

- Long life LED-operating 50,000hrs
- Easy installation using existing socket
- Major power savings
- Voltage: 12VAC/DC, 24VAC/DC, 120VAC, 220VAC
- Choice of 6 colors & infrared
- Lamp base: B22



Fluorescent
Cool white(-C)



incandescent
Warm white(-Y)

Option of White color



20°
Spot
Angle (S)



50°
Wide
Angle (W)

Option of View angle

12VAC/DC 24VAC/DC 120VAV

Option of Volatage

Dimensions of GNL-B22/01



LED LAMP DATA

“S”TYPE

P/N	LED Color	Power 220V/120V/12V	Intensity (lm)	Wavelength (nm)	Viewing Angle
GNL-B22/01-S34UE	Ultra Red	4W/2.2W/2.4W	51	625	20°
GNL-B22/01-S34UY	Ultra Yellow	4W/2.2W/2.4W	51	590	20°
GNL-B22/01-S34UB	Ultra Blue	4W/2.2W/2.4W	40.8	470	20°
GNL-B22/01-S34UG	Ultra Green	4W/2.2W/2.4W	74.8	520	20°
GNL-B22/01-S34UW-Y	Warm White	4W/2.2W/2.4W	64.6	2700K-3500k	20°
GNL-B22/01-S34UW-C	Cool White	4W/2.2W/2.4W	71.4	5500k-7000k	20°
GNL-B22/01-S34-850	Infrared	4W/2.2W/2.4W	408mW	850	20°

“W”TYPE

P/N	LED Color	Power 220V/120V/12V	Intensity (lm)	Wavelength (nm)	Viewing Angle
GNL-B22/01-W34UE	Ultra Red	4W/2.2W/2.4W	51	625	50°
GNL-B22/01-W34UY	Ultra Yellow	4W/2.2W/2.4W	51	590	50°
GNL-B22/01-W34UB	Ultra Blue	4W/2.2W/2.4W	40.8	470	50°
GNL-B22/01-W34UG	Ultra Green	4W/2.2W/2.4W	74.8	520	50°
GNL-B22/01-W34UW-Y	Warm White	4W/2.2W/2.4W	64.6	2700K-3500k	50°
GNL-B22/01-W34UW-C	Cool White	4W/2.2W/2.4W	71.4	5500k-7000k	50°
GNL-B22/01-W34-850	Infrared	4W/2.2W/2.4W	204mW	850	50°